

Room 10C60/10C62. 10F Shanghai Mart Tower
2299 Yan An. Road West, Changning District
Shanghai 200336 China

www.amsupplyasia.com

+86 21 5291 9259

info@amsupplyasia.com

CONTROL VALVE DOUBLE FUNCTION


Reference	AMS-SW002
Mixer body	Brass
Handle	Zinc
Chrome thickness for mixer body (um)	0.25-0.30
Max open angle	25 °
Max turn angle	110 °
Torque	8-12 Nm(Nomal 10 Nm)
Pressure resistance	Min. 45 bar
Working pressure	Max.12 bar
Max. Temperature	90 °
Max sound lever in an edeal body	17-18 db(A) at 3 bar , 21-22 db(A) at 5 bar
Flow rate (D resistance)	(5.5bar)6.5L /min , (1.4bar)9.6L/min (ASME A112.18.1-2005/CSA B125.1-05)
Endurance test	Min 500000 times (ASME A112.18.1-2005/CSA B125.1-05)

OTHERS

»»Life test for single lever mixer :when 0.3MPA. hot water =65 degree +/-2 degree , cold water under or = 30 degree , the endurance is Min 500000 times (ASME A112.18.1-2005/CSA B125.1-05)

»»Spool material :MJ pressure balanced cartridge Ceramic:Al2O3 96%

Details of CONTROL VALVE DOUBLE FUNCTION



Packing Information

Psc per carton	8
Carton size (mm)	465x345x335


PRE-EMBEDDED PART FOR AMS-SW002

Material:



Brass body ,plastic cover

Chrome thickness:

No



Code	The Accessory List	Quantity
1	Shower arm	1
2	Flange	1
3	Shower head	1
4	Main body	1
5	Pretend sleeve	1
6	Plate	1
7	Knob	1
8	Handle	1
9	Screw	1
10	Screw	2
11	Shower outlet	1
12	Screw	2
13	O-ring	2
14	Index	1
15	Allen key	1



Packing Information

Psc per carton

12

Carton size (mm)

475x345x270