

SAFE BOX

Reference	AMS-LB03-U
Material	galvanized steel plate for body and hot rolled steel plate for door
External Dimensions(mm) Width x Height x Depth	420x127 (max. 132) x350
Internal Dimensions (mm) Width x Height x Depth	416x73x346
Volume (l)	9.6
Body thickness (mm)	2
Door thickness (mm)	5
Solid Bolt (mm)	20
Color	Black
Anchorage	4 fixing holes in the base. Include 4*8*40 galvanized steel expansion anchoring units.
Interior mat	Color black, 5 mm thick
Internal light	Yes
Rental	No
Inner socket	Universal socket with USB, which allows you to charge mobile, laptop, iPad, tablet, camera etc.
Door cut and door frame	Cutting machine & bending machine
Net weight (Kg)	10.2
Loading Qty. 20'	1000

OPENING

- »» Opening system: Motorized electronic.
- »» 15 manager codes, through the external control unit.
- »» 6-digit user code.
- »» Braille keypad.
- »» Audit of opening and closing of the last 100 registrations through CEU and software.
- »» NO key for emergency opening.
- »» Powered by 4 AA alkaline batteries.
- »» Screws are made of galvanized steel.
- »» Low battery indicator.

OTHERS

- »» The external unit allows: Initialize the box (date, time, room number). Make emergency openings. Read the last 100 opening and closing records, as well as dump them to a computer for later printing.
- »» It includes software that allows you to display the dump logs on the screen and print them.
- »» Memory Flash-Ram: information is not lost even if it runs out of batteries.
- »» The screws are made of 304 stainless steel.

Details of SAFE BOX

